

Zebra® ZXP Series 8™ Secure Issuance Retransfer Card Printer



SEE MORE. DO MORE.



Provide Financial Cards Instantly

With Zebra's ZXP Series 8 Secure Issuance printer, your financial, educational or retail institution can issue financial cards quickly, securely and without sacrificing print quality. You'll boost customer satisfaction by instantly printing and encoding personalized cards on site.

Secure and Protect Cards and Data

Meeting industry standards for the financial instant issuance market, and custom-coded for leading instant issuance applications, the printer ensures the highest levels of security and reliability. The printer includes physical and logical security locks to protect the input hopper, reject bin, and media inside the printer from unauthorized access and can be physically secured to the work station via a Kensington® lock. AES-128 encryption protects all sensitive cardholder data during network transmission, and the cards are obstructed from view while in the input and output hoppers.

Reduce Operational Costs and Increase Revenue

Instant issuance eliminates the costs and delays of mailing cards from centralized printing facilities and prevents cards from being lost or stolen in the mail. Both the issuing institution and the cardholder gain peace of mind, while card activation rates and cardholder spending rise.

Specifically Designed for Financial Services Instant Issuance Solutions Including

- Bank-issued ATM and credit cards
- Personalized retail gift cards
- Campus debit and cashless cards

ZXP SERIES 8 SECURE ISSUANCE

Security Features

- Obscured card input and output hoppers
- Logical lock for enclosure, input hopper and reject bin with physical key override
- Printer auto lock on power up initialization
- Transfer film easily shows tamper evidence for built-in fraud protection
- Kensington[®] lock slot to secure printer to work station
- K panel ribbon overwrite feature protects unauthorized access to sensitive print data

Superior Performance

- Best-in-class throughput for printing and encoding — due in part to the patent-pending simultaneous 2-sided retransfer process plus efficient landscape print mode — increases your operational efficiency without sacrificing quality
- Based on Zebra's image-processing technology, photo-quality color and resolution are obtained to meet your quality and brand specifications
- Designed inside and out to be reliable and durable — reducing repair costs and downtime

Modular Design With Order-Now or Add-Later Options

- Magnetic stripe encoder
- EMV level 1 smart card contact and contactless encoders

Easy Printer Integration and Management

- Advanced ZMotif[™] SDK enables financial services application providers and system integrators with complete control over printing and encoding card personalization operations
- ZMotif XML-based drivers and SDK makes the printer enterprise-ready with driver and management utility tools for easy setup and faster deployment—saving IT setup time and costs
- Microsoft[®] Windows[®] certified drivers ensure application compatibility, ease of use, and investment protection in existing software infrastructures
- USB and Ethernet connectivity interface options for easy integration into local or networked systems

Genuine Zebra[™] Supplies

- Zebra True Colours i Series intelligent ribbon and transfer film automatically calibrate printer increasing productivity, reducing downtime and minimizing training.
- Choose Zebra for quality plastic cards in a variety of types and materials.
- For high-quality output, rely on genuine Zebra supplies.

Supports Leading Financial Instant Issuance Application Providers

The ZXP Series 8 Secure Issuance printer, combined with the services of leading Zebra application provider partners, provides a complete solution for financial,



retail and campus institutions looking for an instant issuance solution with the highest print quality and security features in the market. Working with leading application providers ensures the highest levels of application reliability and support.

Genuine Zebra[™] Supplies

Genuine Zebra supplies meet stringent quality standards and are recommended for optimal printing quality and proper printer performance. The ZXP Series 8 Secure Issuance printer is designed to work only with Zebra True Colours[®] i Series[™] ribbons and Zebra True Colours[™] i Series transfer film.

For more information, visit www.zebra.com



ABOUT RETRANSFER PRINTING TECHNOLOGY

Unlike traditional direct-to-card printers, which use a printhead that prints through a ribbon directly onto the card, retransfer printers print onto a flexible, transparent film that is then thermally bonded to the card.

In General, benefits of Retransfer Printing include:

- Higher image quality and print resolution
- The ability to print on uneven card surfaces, such as smart cards
- True edge-to-edge printing (via over-the-edge printing). Traditional card printers leave a white border at the edges of the card
- The ability to print on non-PVC cards. Direct-tocard printers require a dye-receiving surface available only through PVC cards
- More durable and abrasion-resistant cards
- Fraud protection, since the film is inherently tamper-evident

Advantages of Zebra's Innovative Retransfer Card Printer

Zebra's ZXP Series 8 Secure Issuance retransfer card printer achieves the fastest print speed while maintaining top image quality, making it the best-inclass retransfer printer available on the market.

- Zebra achieves print speeds that far exceed any other retransfer printer, and that are comparable to many of the fastest direct-to-card printers on the market today.
- Zebra's image-processing technology compensates for image errors normally caused by high printing speeds — enabling photo-quality images and print resolution even at increased print speeds.
- Zebra's patent-pending simultaneous dual-sided image transfer process applies film to both sides of the card in a single pass, drastically reducing the print time.

The result is photo-like image quality and bestin-class throughput for mainstream printing and encoding — so you enjoy increased operational efficiency.





Zebra*Care*[™]

Increase printer uptime and reduce lost productivity and unbudgeted repair costs by selecting a ZebraCare service agreement. A cost-effective means of planning and budgeting for your annual maintenance expenditures, your agreement ensures that trained Zebra technicians will bring your printer back to factory specifications. Zebra offers a variety of plans to fit your budget and business needs.

SPECIFICATIONS AT A GLANC

Printer Name

ZXP Series 8 Secure Issuance

Secure Issuance Features

- · Printer auto lock on power-up initialization
- · Application-specific and software SDK printer unlock command for card input, reject bin and printer
- Mechanical security lock and key override with unlock override thumbwheel
- · Obscured, locked access 150 card capacity feeder (30mil)
- · Locked access 15 card reject hopper (30mil)
- Obscured 100 card output hopper (30mil)
- · Kensington physical lock capable
- AES 128 encryption of encoding data
- · Printer driver/SDK phase key for printer/driver authentication
- K panel ribbon overwrite feature protects unauthorized access to sensitive print data

Standard Features

- USB and Ethernet connectivity
- · Single-card feed capability
- · 150 card capacity feeder (30mil)
- 15 card reject hopper (30mil)
- 100 card output hopper (30mil)
- i Series[™] intelligent media technology
- Auto-calibration of media
- · 21-character, 6 line LCD operator display
- · 304 dpi (12 dots/mm) print resolution
- · 64MB memory standard
- · Lifetime warranty on printhead
- 2-year limited warranty on printer
- Microsoft[®] Windows[®] certified drivers

Printing Specifications

- · Dye sublimation retransfer
- · Full color or monochrome retransfer printing
- · Single- and dual-sided printing
- Max print speed single-side 190cph*
- · Max print speed dual-sided 180cph*
- Photo quality image

ZEBR/

SEE MORE DO MORE.

www.zebra.com

- Over-the-edge printing on standard CR80 cards
- * Print speed based on click to drop, average print coverage, with USB connectivity, card per hour (cph).

Encoding Options & Specifications

- Smart card contact station: ISO 7816
- · Magnetic stripe encoder: ISO 7811 and JIS-II (high and low coercivity)
- EMV level 1 combined MIFARE® ISO 14443 (13.56MHz) and ISO 7816 contact encoder
- · Encoding over Ethernet (external USB bridge device

*Specifications subject to change without notice.

ASIA-PACIFIC HEADQUARTERS Zebra Technologies Asia Pacific Pte Ltd

Middle East & Africa: Dubai, South Africa

Other Locations

ZMotif Software

Microsoft Windows Certified Printer Drivers Supported: Windows XP, Windows Vista®, Windows Server® 2003, Windows 7

32bit and 64bit compatible.

Driver Features

- Graphical card orientation setting to visualize card printing setup and configuration
- Card source and card type selection
- Complete graphical control over area and element selection of black extraction parameters
- Auto sensing of ribbon type and smart card encoding options

Toolbox Utility Features

- Printer configuration tools and utilities for complete control over all printer functions and features
- Optional password protection settings and user role-based security settings prevent accidental or unauthorized driver or printer configuration changes
- Complete technology card management enables setup and testing of all printer and encoder features and functionality
- Printer test cards and diagnostics utilities ensure error-free printing and fast troubleshooting capabilities

XML-Based SDK

- Downloadable SDK for custom application . integration
- XML-based SDK enables third parties to quickly add advanced print and encoding features
- Capabilities include direct access to PC/SC Smart Card encoder driver and XML-based job control print job specifications
- Support for complete Uv printer and inhibit pane support

Card Specifications

- · Support for EMV certified cards
- Card thickness: 30~40mil
- Card size: ISO 7810 format, Type ID-1, CR-80 size
- Card material: PVC and composite, ABS cards, PET, PET-G, Teslin® composite, and polvcarbonate*
- Specialty cards: transparent (IR-blocked) or translucent card 30 mil (clear and colored)*
- Technology cards: contact and contactless smart cards, UHF cards*
- ** Please contact your Zebra reseller for qualification of cards

Options and Accessories

71 Robinson Road, #05-02/03, Singapore 068895 T: 65 6858 0722 F: 65 6885 0838

New Zealand, Philippines, South Korea, Singapore, Thailand, Taiwan, Vietnam

USA: California, Georgia, Illinois, Rhode Island, Texas, Wisconsin

Latin America: Brazil, Florida (LA Headquarters in USA), Mexico

Extended product warranty programs

Asia-Pacific Sales Representations: Australia, China, Hong Kong, India, Indonesia, Japan, Malaysia,

Europe: France, Germany, Italy, the Netherlands, Poland, Spain, Sweden, Turkey, United Kingdom

©2014 ZIH Corp. CardSense, i Series and all product names and numbers are Zebra trademarks, and Zebra, the Zebra head graphic and True Colours are registered trademarks of ZIH Corp. All rights reserved. Kensington is a registered trademark of ACCO Brands Corporation. Microsoft, Windows, Windows, Server, Windows Vista are either registered trademarks or trademarks of Microsoft Corporation. MIFARE is a registered trademark of Philips Semiconductors Gratkorn GMBH Ltd. Teslin is a registered trademark of PPG Industries. HID and iClass are registered trademarks of HID Global Corporation. All other trademarks are the property of their respective owners.

Operating Characteristics

Environmental

- Operating Temperature: 59°F/15°C ~ 77°F/25°C
- Storage Temperature: 23°F/-5°C ~ 131°F/55°C
- · Operating Humidity:
- $20\% \sim 80\%$ inclusive, non-condensing Storage Humidity:
- 10% ~ 90% inclusive, non-condensing Shipping Temperature:
- -40° F/ -40° C $\sim 140^{\circ}$ F/ 60° C Shipping Humidity:
- 10% ~ 90% inclusive, non-condensing Media should not be above 140°F/ 60°C for
- longer than 200 hours, and above 90% relative humidity at 104°F/ 40°C for longer than 100 hours

Electrical

- Single-phase AC power
- 100~240V AC and 50~60HZ

Communications Interfaces

- USB V2.0
- 10/100 Ethernet

Physical

Printer

- Height (w/card hoppers): 13.2"/ 334mm
- Width (w/card hoppers): 18.75"/ 476mm
- Width (w/card hoppers, w/laminator): 30.75"/781mm
- Depth: 20.4"/ 519mm
- · Weight (printer only): 27.5 lbs/ 12.5kg
- Weight (printer, laminator): 44 lbs/ 20kg

Supplies

• Zebra i Series intelligent technology uses RFID tags to authenticate and automate color ribbons and transfer film

: 500 images/roll

: 500 images/roll

: 415 images/roll

P1030934 (8/14)AP

Cleaning supplies

YMCKI 5 panel

YMCKKI 6 Panel

Clear and holographic:

True Colours i Series Ribbon

 YMCK 4 panel 625 images/roll

• Monochome black : 2500 images/roll

1250 single-sided/ 650 dual-sided cards/ roll

NOTE: For optimum print quality and printer

performance, use genuine Zebra[™] supplies.

True Colours i Series Transfer Film

• YMCKK 5 panel : 500 images/roll • YMCUvK 5 panel